






There is no faster way!

Targeted troubleshooting with pump and the associated covers quickly localises escaping cooling fluids. This puts an end, once and for all, to constantly having to replenish liquids escaping at the vehicle.

Our quality guarantee:

Made in Germany!

Development and production in Germany guarantee that the cover is a perfect fit for the expansion tank.



4800

Cooling pump and adapter

Components

Made in Germany

HAZET No.	4000896+
 Cooling pump Up to 2.5 bar 4800-1 	022243
Intermediary piece, flexible hose	022243
4800-2	022274
Amazone Pantera CLAAS Jaguar, Lexion, Scorpion, Ares, Atles, Ceres DAF 45 model year 05/1991 — 12/2000 DOOSAN Wheel excavator S · Caterpillar excavator DX FENDT KAESER Mobilair LIEBHERR A308-316 MASSEY FERGUSSON with tank no. 180224M92 and 4296015M1 MERCEDES-BENZ Vito · Viano · Solaris NISSAN Forklifts PUTZMEISTER BSA 1409 SCANIA Vabis Case Quadtruc, Magnum 4800-3	022281
DEUTZ Engines 3.6 PowerPack · BF6M1013FC · TCD2013L6 2V and 4V Genset 250kV	022201
HATZ 4H50tic IVECO Eco Daily with blue lock Case Puma, SBS, LBS, Optum, Maxxum, CVX New Holland TVT, T7, T7 Elite Pack, T6 FENDT Vario model year 2000 → Combine harvesters L series CLAAS Arion, Axion	
4800-4 A	156504
 COMPAIR Mobile compressor with VW expansion tank FENDT Farmer 300 model year 1988 → · Type 500 · Type 700 · Vario model year 1988 → 2000 LINDE forklifts PUTZMEISTER BSA 1407D · BSA 2110 HP-D RENAULT Midlium model year 01/2000 → 12/2013 Volvo FE model year 05/2006 → · FL model year 03/2000 → 	
4800-5 A	161843
 DEUTZ Engines KHD1015 · D2008 · D2009 · TD2.9 L4 · TCD3.6 · BFM1013 · BFM2012 · TCD2013 2V · BFM1015 · TCD2015 V8 · V6 · M · TCD 12.0 and 16.0 MERCEDES-BENZ Sprinter model year 1999 → Type 170 · 208 · 611 4800-16 	098507
MERCEDES-BENZ Sprinter from 2006, Viano from 2003	030301
4800-18	128815
IVECO Euro-Star · Euro-Tech · Euro-Truck · Daily with black lock MAN F90 · F2000 · TGA model year 03/2000 → · TGL model year 04/2005 → · TGM model year 10/2005 → · TGS model year 10/2007 → 01.2012 · TGX model year 10/2007 → 01.2012 MERCEDES-BENZ Commercial vehicles Actros · Atego 1217 model year → 1999 · Eco 8401 · SK1728 Antos · Arocs · Atego model year 1998 → 2013 · Axor model year 09/2001 → 10/2004 · Econic · Zentros • CLAAS Xerion, Tucano	
4800-20	144242
Volvo Commercial vehicles Scraper tractor dumpers	
4800-21 A	162185
ISUZU Trucks MITSUBISHI Commercial vehicles Fuso Canter NISSAN Forklifts YALE GDP/GLP 16-30	
4800-23	144273
MAN Buses such as Lions Coach · Lions Star · Lions Comfort · Lions City MERCEDES-BENZ Citaro model year 01/1998 4800-25	202857
• DAF CF and XF Euro 6 from 2013	203857
• DAF CF and XF EUro 6 from 2013 4800-26	214495
MERCEDES-BENZ Atego from model year 2014	2.7100
4800-27	214501
MERCEDES-BENZ Actros EURO 6 with HEYCO expansion tank since 2014	
4800-28	214518
• SCANIA 143, G-/P- and R series 4800-29	222780 I







4800/3, EAN-No. 4000896200047

Commercial vehicle radiator tester

• To test for leakage in radiators and heating circuits with pressure build-up. e.g. on MAN trucks and buses, NEOPLAN, MERCEDES-BENZ trucks and buses, as well as agricultural machinery and construction vehicles

• Incl. cover 4800-20



4802-1, EAN-No. 4000896200030

Commercial vehicle vacuum radiator filler

- New design of the vacuum radiator filler allows the desired vacuum to be reached faster, which allows the cooling system to be filled more quickly
- Fast cooling fluid flow rate: approx. 80 l in 20 minutes
- · No cooling fluid is lost through the cooling system overflowing
- Separate control through the diagnostic testing device is no longer necessary
- Vacuum leakage test before refilling the cooling system
- Bubble-free filling of the cooling and heating circuit in trucks, buses, agricultural machinery and construction vehicles
- · Can be used together with single or universal adapters

















The illustration on the title page was created by the Brazilian artist and comic book author **Nik Neves**, who currently lives in Berlin.

Inspired by much of his time spent travelling, he has developed a unique style that can often be found in or on illustrated maps, book covers, comics or calendars, for example.

His work has appeared in "Illustration now! 5" and "Mind the Map" published by "Taschen GmbH, Cologne" and "Die Gestalten Verlag GmbH & Co.KG, Berlin", amongst other publications.







4800/8, EAN-No. 4000896216499

Radiator adapter case for commercial vehicles

- Checking for leakage in cooling systems and heating circuits
- 4800-1 Cooling pump to 2.5 bar
- 4800-2 Intermediary piece, flexible hose
- 4800-3 Radiator adapter for DAF 45 model year 05/1991 → 12/2000, DOOSAN Wheel excavator S, Caterpillar excavator DX, KAESER Mobilair LIEBHERR A308-316, MERCEDES-BENZ Vito, Viano, Solaris, NISSAN forklifts, **PUTZMEISTER** BSA 1409, **SCANIA** Vabis
- 4800-5 A Radiator adapter for COMPAIR mobile compressor with VW expansion tank, LINDE forklifts, PUTZMEISTER BSA 1407D BSA 2110 HP-D, **RENAULT** Midlium model year $01/2000 \rightarrow 12/2013$, **Volvo** FE model year $05/2006 \rightarrow FL$ model year 03/2000 - FL
- 4800-25 Radiator adapter for MAN buses such as Lions Coach, Lions Star, Lions Comfort, Lions City, MERCEDES-BENZ Citaro model year 01/1998, **IVECO** Euro-Star, Euro-Tech, Euro-Truck, Stralis, Daily with black lock, **MAN** F90, F2000, TGA model year $03/2000 \rightarrow$, TGL model year $04/2005 \rightarrow$ TGM model year $10/2005 \rightarrow$, TGS model year $10/2007 \rightarrow 01/2012$, TGX model year $10/2007 \rightarrow 01/2012$, **MERCEDES-BENZ** commercial vehicles Actros, Atego 1217 model year \to 1999, Eco 8401, SK1728 Antos, Arocs, Atego model year 1998 \to 2013, Axor model year 09/2001 \to 10/2004, Econic, Zentros
- 4800-26 Radiator adapter for **DAF** CF, XF Euro 6 model year 2013 \rightarrow 4800-27 Radiator adapter for **MERCEDES-BENZ** Atego model year 2014 \rightarrow
- 4800-28 Radiator adapter for **MERCEDES-BENZ** Actros EURO 6 with HEYCO expansion tank model year 2014 \to **MAN** TGX, TGS EURO 6 with HEYCO expansion tank model year 2012 \to
- ullet Classification to vehicles: www.hazet.de ullet The Tool Finder ulletRadiator adapters 4800





4800/6, EAN-No. 4000896216482

Radiator tester for agricultural machinery

- Checking for leakage in cooling systems and heating circuits
- 4800-1 Cooling pump to 2.5 bar
- 4800-2 Intermediary piece, flexible hose
- 4800-3 Radiator adapter for **AMAZONE** Pantera, **CLAAS** Jaguar · Lexion · Scorpion · Ares · Atles · Ceres, FENDT, MASSEY FERGUSSON with tank no. 180224M92 and 4296015M1, CASE Quadtruc · Magnum
- 4800-4 A Radiator adapter for CASE Puma · SBS · LBS · Optum · Maxxum · CVX, **NEW HOLLAND** TVT · T7, T7 Elite Pack · T6, **FENDT** Vario model year 2000 \rightarrow · Combine harvester L series, **CLAAS** Arion · Axion, **DEUTZ** engines 3.6 PowerPack · BF6M1013FC · TCD2013L6 2V and 4V
- 4800-5 A Radiator adapter for **FENDT** Farmer 300 model year 1988 → Type 500 · Type 700 · Vario model year 1988 → 2000
- 4800-20 Radiator adapter for CLAAS Xerion · Tucano as well as all new CLAAS machines with MERCEDES-BENZ expansion tank
- ullet Classification to vehicles: www.hazet.de ullet The Tool Finder ulletRadiator adapters 4800

tools necessary.

Top speed repairs

The striking faces on the wrench mean you can

Our quality guarantee: Made in Germany!

Thanks to our very high quality standard, the tool

withstands even the harshest conditions in any

20 34 Commercial vehicle box end wrench

• 12-point profile facilitates application even on hard-to-reach fittings

HAZET torque wrench in accordance with the manufacturer's specifications

• Wrench with 29 3/4 4-point insertion hole for the correct tightening of screws with

• Wrench flat with laser-engraved formula for calculating the correct effective length

(12-point) with 2 striking faces

loosen the fitting with just the hammer, no further

such as brake calliper fittings.

commercial vehicle workshop.


strong power transmission to highly stressed components,






2872 SZ































































2872 SZ-24

Commercial vehicle cardan shaft striking face wrench

For the operation of the brake calliper fitting on, e.g.

SAF-brake calliper, MERCEDES-BENZ Atego and Actros

MERCEDES-BENZ Atego, Actros, KÄSSBOHRER buses

- an repairs on the go, where no working pit is available
- Enables the usually very tight cardan shaft bolt connection to be removed, even when the space available is limited • Including laser engraved formula for rapid conversion of the tightening torque specified by the manufacturer
- 2 impact areas enable the force to be applied using a hammer

DAF XF95/XF105/XF

• Highly stable and extremely resilient






s 24

s 26

219.0

219.0

220.5



20 3/4"

EAN-No.

4000896-

204175

203727


207183

215638

s 21

2872 E


TORX® slogging wrench with 2 striking faces



• Use of the wrench for assembly and disassembly of the brake calliper fittings renders disassembly of the steering tie lever unnecessary


• Correct tightening of screws with torque wrench using a 29 % drive in accordance with

the manufacturer's specifications • For e.g. MAN TGL TGM wrench sizes: E18, E20, E24 • 2872-E20 e.g. on Schmitz Cargobull Trailer axles



20 3/4"

Made in Germany EAN-No. length thickness 4000896+ 201235 2872-E18 20 3/4 215 573 E 18 120 30 12 2872-E20 E 20 20 3/4 216 577 120 32 12 201242 2872-E24 20 3/4 201259





MAN cardan shaft fittings

4937-21

13

125 1/2 Commercial vehicle box end wrench (12-point) with 2 striking faces

- For loosening or tightening brake cylinder fittings
- Use in trucks, buses, trailers and trailer axles without removing the wheel
- No need to remove the wheel, even if brake cylinder fittings protrude far into the rim
- Laser-engraved formula for rapid conversion of the tightening torque specified by the manufacturer
- 2 impact areas enable the force to be applied using a hammer
- Drive 125 1/2









Made in Germany

4969-612, EAN-No. 4000896204281

Compressed air quick-connector releasing tool

- Easy loosening of quick-connectors with Ø 6, 8, 10, 12 mm
- For operation with open-end s 13 mm (HAZET 600 N-13), no further tools necessary
- For plug connectors DIN 74324 6 x 1.0, 8 x 1.0, 10 x 1.0, 12 x 1.5, 12 x 2.0 mm
- Enables separating contaminated tubes and plug connectors
- To be used by one person
- Prevention of injuries
- Time-saving and therefore also cost-saving

No further tools necessary!









Made in Germany

2784-14, EAN-No. 4000896155583

20 3/4" **Brake calliper** screwdriver socket

For the operation of the brake calliper screws (KNORR-BREMSE) on MERCEDES-BENZ trucks e.g. Actros







4971-11, EAN-No. 4000896**218257**

Brake calliper readjusting tool KNORR-BREMSE

- For operation of the readjusting tool on disc brakes **KNORR-BREMSE**
- For readjusting the brake calliper KNORR-BREMSE via nut-driver
- Special 11 tooth profile
- Suitable for brake callipers KNORR-BREMSE on trucks, buses, trailers and trailer axles of all brands



125 1/2



2784 S

Impact socket (special profile) **MERCEDES-BENZ**

- Optimised special profile for damage-free attachment of the flat-head
- For the operation of the lightweight nuts on the frame, fifth-wheel coupling, front carrier and vibration damper with special profile MERCEDES-BENZ on the Actros, Antos, Arocs model year 2016 -
- Surface: phosphatised
- Output: groove profile





2784-T60/4, EAN-No. 4000896188611

4968-1618, EAN-No. 4000896177684

• Blades Ø 16 mm on 18 mm

• Functional length: 85 mm

Commercial vehicle ABS reamer • For cleaning the ABS sensor receptacle e.g. on all MAN trucks

Brake disc screwdriver socket set

- For impact operation
- For the operation of the brake disc screws on MERCEDES-BENZ Actros 2nd generation since model year 2011
- Total length: 120 mm





EAN-No. HAZET No 4000896+ MERCEDES-BENZ special profile, short 2784 S-1 46 138 213252 2784 SLg-1 MERCEDES-BENZ special profile, long 218240

















16

Made in Germany

20 3/4" 🛂




















































































































































































































Application example complete with brake calliper holder



4972-2, EAN-No. 4000896**215393**

 For disassembly and assembly of brake callipers in trucks, buses, trailers and trailer axles that are installed in a diagonal "clockwise position between 8 o'clock and 5 o'clock"

• Together with brake calliper holder HAZET-No. 4972-1

• Connect swivel bearing to brake calliper holder and position with e.g. jacking carriage below brake calliper. This enables easy insertion of the screws even

Made in Germany

Swivel bearing

in awkward positions

4972-1/3, EAN-No. 4000896**215799**

Commercial vehicle lifting aid

- Allows you to work safely, without straining your back, in tight
- spaces in the wheel arch on trucks, buses, trailers and trailer axles • Significantly easier work when assembling and disassembling brake callipers
- and wheel hubs thanks to lifting aid
- No strain on the back
- Second person not required
 Makes screw tightening easier
 Secure hold for heavy components
 Easy handling possible

 Takes the various installation either.
- Takes the various installation situations of the brake calliper into consideration
- Secure hole of the brake calliper/wheel hub in or on the socket
- Secure movement with suspended components
- One-hand operation possible via spindle
- Contents: - Brake calliper holder

- Wheel hub retaining tool













NEW!


Made in Germany

















4972-1, EAN-No. 4000896**215423**

commercial vehicles

• Easy to use

• Makes screw tightening easier

Second person not required





Pitstop in record time for your thread repair

- Smooth and effortless maintenance of a defective thread
- Chipless thread restoration
- No replacement of expensive vehicle components through new professional repair option
- Maintenance of components often possible in the installed state
- Extremely practical tool also facilitates work in areas with restricted access (especially with large diameters)
- Strength of the component is retained
- Even the beginning of the thread is shown again without any problems
- Easy manual operation without much physical effort
















843-2/9, EAN-No. 4000896200559

For threads:

Ø 10-36 mm

Made in Germany























Set new bush and tool

4937-2/32, EAN-No. 4000896222957

Tool set for silent blocks • For reliably pressing slotted silent blocks in and out • Significant time saving, as no axle parts need to be removed

• MERCEDES-BENZ Actros 1, 2, 3 since model year 2002 – Stabiliser bearings

Ø 60 mm: MAN TAG, TGS, TGX – Leaf spring bearings front axle, rear axle;
 MERCEDES-BENZ Actros, Axor – Leaf spring lug;
 IVECO Eurostar – Leaf spring lug;
 RENAULT Kerax, Magnum, Premium – Leaf spring lug

Ø 70 mm: MAN TGA, TGS, TGX – Shock absorber bearings
 Ø 68 mm: MAN (Font spring) ROR, SAF – Shock absorber bearings

• Ø 58 mm: **MERCEDES-BENZ** 3229 B, 652, 650; **Volvo**

• Optional use of hydraulic cylinder (e.g. HAZET 4932-17) possible • Centring the bush during installation ensures safe operations,

• Pulling in the slotted silent block using the spindle

• Ø 56 mm: **IVECO** Eurostar – Cab

no more canting when pressing in

4932-17, EAN-No. 4000896**15974**1

• Working pressure (max.): 700 bar

• Convenient spring reset

Hollow piston cylinder

• Compact hydraulic cylinder with a capacity of 17 tons

• For threaded spindle 4932-TR20 and nut 4930-2

One-man operation





















































































































































































NEW!











4932 N-100, EAN-No. 4000896187195

Hydraulic foot pump,

• Pump head and tank made of aluminium

• Foot-controlled drain valve, precisely adjustable

Transport interlock

Piston stroke: 23 mm

Big pedal













Defective bush

Installed bush







Ø 66 mm: IVECO Eurostar – Cab
 Ø 65 mm: MERCEDES-BENZ Actros 1; Atego 1; Axor 1, 2, 3; Econic 1 – Stabiliser bearings
 Ø 63 mm: DAF

32

Pull out defective bush







We accept no liability for printing errors!

You decide whether to work by machine or manually! Our pin and axle nut sockets make both possible.


Our products have extremely high dimensional accuracy, thereby permitted high power transmission.

Multiple applications with special wrenches.





- For dismantling / assembly work on the rear axle as well as repair and maintenance work on the wheel hub, wheel bearing or brake disc
- MERCEDES-BENZ hub-reduction axle, such as trailing axle NR7/4
- MERCEDES-BENZ hub-reduction rear axles (Euro-axles) 10 t and 13 t,
- MERCEDES-BENZ hub-reduction axle 7 t AL7/1
- Inside Ø: 101.5 mm
- Length including guide tube (total): 140 mm • 12 pins, width of pins: 11.4 mm
- With 3 replaceable guide tubes
- Outside Ø: 50, 51, 53 mm
- Length (total): 85 mm



20 3/4" 🛂

Ø 110 mm

20 3/4" -4

4937-62, EAN-No. 4000896199020 20 3/4" **Commercial vehicle pin** wrench for rear axle **MERCEDES-BENZ**

• Pin wrench for rear axle nuts


- MERCEDES-BENZ Actros, Atego (heavy design): LN2, SK rear axle
- With outside guide collar
- Inside Ø: 62.8/70 mm
- 6 inside pins,
- width of pins: 7.5 mm • Length (total): 85 mm



Made in Germany







Slotted nut

4937-80, EAN-No. 4000896**199006**

Commercial vehicle axle nut socket, 8-point, s 80 mm

- For dismantling/assembling the front axle nut with 8-point in front of the brake disc
- SCANIA series R, series 4, series 124 I 144 I etc.
- Suitable for impact wrench, e.g. HAZET 9013 M
- · Precise fit

• Parallel surfaces for perfect force fit on axle nuts • Solid design: high (shape) stability even with very high loosening or tightening torques



4937-103/3, EAN-No. 4000896199259

Commercial vehicle pin wrench set for rear axle MAN and MERCEDES-BENZ

• For repair and maintenance works on the wheel hub, wheel bearing or brake disc

HAZET

- For MAN and MERCEDES-BENZ 10 t and 13 t AP Hypoid and trailing axle N7/4, Omnibus 0305G, 0405G
- MAN hub-reduction rear axle F series H7, HD7
- Hypoid rear axle F series HY-1175, HDY-1175
- Inside Ø: 103 mm

- Length (total): 135 mm



4937-117/2, EAN-No. 4000896199242

Commercial vehicle pin wrench set for rear axle MERCEDES-BENZ

• For repair and maintenance works in the rear axle area • For MERCEDES-BENZ Actros, Hypoid rear axle HL, HL 8

 Inside Ø: 117 mm Length including guide tube (total): 200 mm

• 6 pins, width of pins: 9.8 mm


• With guide tube

 Outside ∅: 60 mm • Length (total): 185 mm









We accept no liability for printing errors! www.hazet.de

Slotted nut Made in Germany



4937-7588, EAN-No. 4000896202003

Commercial vehicle mounting sleeve SAF thread M75 x 1.5 right/left

- The sleeve has both a left-hand and a right-hand thread M75 x 1.5
- For SAF axles with disc and drum brakes with Ø 88 mm bearing seat
- Only lift the approx. 40 kg bearing unit (bearing + brake disc + wheel hub) onto the mounting sleeve once, then push up to the bearing seat with \varnothing 88 mm
- Outside Ø: 88 mm

• Drive via lateral rod or without additional tools is possible (handle surface)





4937-100, EAN-No. 4000896**201983**

MAN commercial vehicle mounting sleeve thread M100 x 1.5

- Mounting sleeve to protect the thread on the axle during bearing disassembly and assembly
- Use with MAN TGX, TGA, TGS e.g. for MAN HY 1350 axle (13 t)
- Only lift the approx. 40 kg bearing unit (bearing + brake disc + wheel hub) onto the mounting sleeve once, then push up to the bearing seat with Ø 105 mm
- Thread: M100 x 1.5
- Outside Ø: 105 mm
- Drive via lateral rod or without additional tools (chequered handle surface) is possible



Made in Germany



4937-7582, EAN-No. 4000896**201969**

MAN commercial vehicle mounting sleeve – thread M75 x 1.5

- Mounting sleeve to protect the thread on the axle during bearing disassembly and assembly
- Use with MAN TGL, TGM, L series, HL 2
- Only lift the approx. 40 kg bearing unit (bearing + brake disc + wheel hub) onto
- the mounting sleeve once, then push up to the bearing seat with \varnothing 82 mm
- Thread: M75 x 1.5
- Outside Ø: 82 mm
- Drive via lateral rod or without additional tools is possible (chequered handle surface)





4937-111/2, EAN-No. 4000896**201945**

MAN commercial vehicle pin wrench set for rear axle

- For MAN TGX, TGA, TGS e.g. rear axle: HY 1350
- 4-point drive: 25 mm = 1" as well as outside 6-point: s 60 mm
- 6 pins, width: 11 mm
- Inside Ø: 134.5 mm
- Inside Ø (pin-pin): 118 mm
- Outside Ø: 148.5 mm







25 1" 60

4937-7578, EAN-No. 4000896201990

MERCEDES-BENZ commercial vehicle mounting sleeve – thread M75 x 1.5

- Mounting sleeve to protect the thread on the axle during bearing disassembly and assembly
- Use in **MERCEDES-BENZ** Atego, Atego 2, Tourino
- Only lift the approx. 40 kg bearing unit (bearing + brake disc + wheel hub) onto the mounting sleeve once, then push up to the bearing seat with
- Thread: M75 x 1.5
- Outside Ø: 78 mm
- Drive via lateral rod or without additional tools is possible (chequered handle surface)





4937-110/4937-120

Commercial vehicle hub cap socket, Ø 110 mm and 120 mm for flat oval BPW hub cap

• For **BPW** Eco and Eco Plus axles

ullet Perfect fit for **BPW** contour \varnothing 110 mm, or \varnothing 120 mm

Drive

25 **1**


20 3/4



HAZET No

4937-110

4937-120



110

141

EAN-No.

4000896

199273

210459









3 applications -

1 wrench!



Commercial vehicle axle nut sockets













4937-92, EAN-No. 4000896201952

Commercial vehicle pin wrench for front axle MAN

- Pin wrench for: **MAN** trucks: E 2000 (ÖAF), F 2000, M 2000 L, M 2000 M
- MAN TGA, TGM, TGS, TGX
- MAN buses: Lions City, Lions Classic, Lions Coach, Lions Regio, Lions Star as well as older constructions (models), chassis cabs
- NEOPLAN Citvliner, Starliner, Tourliner, Trendliner
- TEMSA Diamond, VISEON high-decker
- Drive: 20 ¾
- Diameter: 114 mm





Commercial vehicle axle nut socket set **DAF, RENAULT, Volvo**

- 6-point output: s 105 mm
- Drive: 25 mm = 1" and outside 6-point s 60 mm
- Screw-in guide tube allows for flexible application
- DAF with quide tube
- RENAULT, Volvo without guide tube · With outside guide collar



25 1" 60 🛂

Made in Germany



20 3/4" 16

4937-87/3, EAN-No. 4000896**199235**


Commercial vehicle pin wrench set for MAN, MERCEDES-BENZ

- For repair and maintenance works on the wheel hub, wheel bearing or brake disc
 For e.g. MAN TGL front axle since 2000 and L 2000 MERCEDES-BENZ Atego
- rear axle HL2, 814 Vitaro
- Pin wrench for rear axle, inside Ø: 87 mm
- Length (total): 65 mm
- 6 pins, width of pins: 10 mm With 2 replaceable guide tubes
- Outside Ø: 49 mm, 57 mm • Length including guide tube (total): 140 mm










20 3/4" 🛂





772-2/16, EAN-No. 4000896161041

Universal axle and slotted nut wrench set

- For removal and precise installation, e.g. with 6-point and 8-point nuts, slotted nuts, face nuts, round nuts with drilled holes, round nuts with pin holes, etc.
- Clamping range: 35–170 mm
- Torque (max.): 700 Nm
- ☐ drive 20 = ¾"
- 16-pieces in HAZET Safety-Insert-System soft foam insert









Twin tyres, separating tool


- Easy separation of hard-to-access outside twin tyres
 Suitable for axles with disk and drum brakes
- Hand operated tool, low use of force
- Suitable for tractors, buses, trailers and trailer axles

- Operating principle:
 Insert thrust blocks through rim holes with a spindle
 Spindle applies required force and disconnects outside twin tyres from the hub
- Contents (4-piece set):
 1 rim flange support with spindle mount (ball), Ø 44 mm
 1 spindle M24 x 2.0 with 6-point drive s 17 mm
 1 thrust block size 1 Ø 48 x 40 mm
 1 thrust block size 2 Ø 50 mm









s **17 mm**



Place the rim flange support on the socket at the end of the spindle



Select one of the two thrust blocks (abutment) depending on the rim's construction type and screw it onto the spindle



Place the unit in a rim hole. Attention: The rim flange support groove must fit perfectly onto the rim flange of the rear rim



Now operate the spindle until the thrust block (abutment) lies against the inside of



Rotate the spindle drive size 17 until the outside rim disengages from the inner rim

















1790 **Ball joint puller**

- · For trucks, busses and building machinery
- For the easy extraction of ball joint pivots and safe removal of ball joints
- · Supported by hydraulic system
- Load (max.): 12 t



HAZET No.	Q mm	sb mm	EAN-No. 4000896+
1790-5	30-34	70	145461
1790-6	36-40	85	145478

4961 N-23/12, EAN-No. 4000896186754

Wheel hub grinder

- For optimal cleaning of wheel hubs and brake discs
- · Hook and loop fastener for quick changing of grinding wheels
- With 6-point socket for firm hold at the device
- 8-point profile for safe and firm fixation
- \bullet Inside \varnothing (max.): 23 mm Grinding wheels Ø: 56 mm

For stud bolts! No wheel hub chippings!








125 1/2 🛂

202010




1779-3, EAN-No. 4000896135998

Universal ball joint puller

- Universal application e.g. for trucks, lightweight design
- Jaw opening a: 32 mm
- Clamping range sb: 85 mm







Made in Germany

652/653

Tyre lever

Heavy design

Made in Germany

EAN-No. HAZET 4000896+ 028702 652 600 653 456 028719



4937-26/3, 4937-27/3

Commercial vehicle centring sleeve set

- For fast assembly of centred truck drop centre rim wheels for rim hole Ø 26 mm
- No damage of the thread as well as exact centring of the rims through conically cranked sleeves



668-2, EAN-No. 4000896204830

Commercial vehicle sensor assembly tool for Conti Pressure Check (CPC)

- Very easy application, very fast assembly, just a few seconds per sensor
- For quick, precise and above all damage-free work on trucks, buses, construction and agricultural machinery
- Exact positioning of the sensor in the rubber container
- If a tyre has to be replaced due to damage or wear, only a new, cheap rubber container is glued in the new tyres. The valuable available sensor is now simply inserted again with the HAZET No. 668-2 sensor tool




20 3/4″ 25 **1**″

20 3⁄4″

1790-3, EAN-No. 4000896145454 **Ball joint puller**

• For extracting the ball joint pivots of


- steering arms, steering tie rods, stabilisers
- Jaw opening a: 40 mm
- Clamping range sb: 85 mm



1779-55, EAN-No. 4000896136407

Ball joint puller

- For removing the ball joint pivots of steering tie rods, stabilisers, etc.
- Jaw opening a: 55 mm
- Clamping depth st: 80 mm
- Width *b:* 77 mm
- For e.g. commercial vehicles MAN, MERCEDES-BENZ, etc.



1004 S

4937-27/3

Impact socket (6-point)

7/8"-11G e.g. **SCANIA**

- DIN 3129, ISO 2725-1
- Wrench size: 32 mm

1004 S-32 20 34"

- Especially long 6-point nut-driver design e.g. for deep wheel nuts and bolts
- on commercial vehicles For impact operation
- Surface: phosphatised

1004 S-33 20 34"

- Extra long design
- E.g. for deeply located wheel nuts and bolts on commercial vehicles
- With borehole for locking pin or safety spring and groove for o-ring • DIN 3129, ISO 2725-2

1104 S-32 25 1"

- · For impact operation
- With bolt for locking pin retaining Surface: phosphatised



HAZET 1004S-32




Your fast and innovative problem solver!

Thanks to our in-house engineering and development facility in plant 1 in Remscheid, our products are not just innovative, they feature HAZET-like dimensional accuracy and extreme precision.

This guarantees very high power transmission, which in turn permits a fast repair.

In addition, our products are matched specifically to the application concerned, generally making operations much easier.



(10 3/8



Injection line wrench DAF

• The special design of the socket ensures proper seat of the injection line fitting Application:

125 1/2

For the operation of the union nut on the high-pressure line on the injection valve-common rail injection system

- Open 12-point socket for the operation of screwed connections on
- The tightening torque required by the manufacturer is achieved
- by using a HAZET torque wrench (observe manufacturer specifications)
- DAF Euro 6 engines MX11/MX13 e.g. XF, CF • Surface: burnished





4550-3, EAN-No. 4000896104307

Injection line wrench

• Open 12-point socket for the operation of screwed connections on injection lines • For the operation of screwed connections on injection lines of **MAN** trucks



with D 20 engines - Common Rail injection systems



2849-15, EAN-No. 4000896159284

Turbo charger wrench

- Loosen and tighten turbocharger nuts on MAN trucks
- Bent form of the box-end wrench is especially adapted to the confined spaces





Made in Germany

2871 E-12, EAN-No. 4000896**201730**

Turbocharger/manifold TORX® socket • For operating the turbocharger and manifold screws on MAN TGL,

TGM with E08 engines

 Operation e.g. with ratcheting combination wrench 606-17 or insert box-end wrench 6630 d-17 and tool holder 6397 (screw loosening) with torque wrench 6292-1 CT (screw tightening)



4558, 4558-1, 4558-2

Pressure nut pin wrench

• For the operation of the compression nut at the nozzle holder



HAZET

4000896+ For MAN and MERCEDES-BENZ trucks M 401/421, M 402/422, LA, A, M 403/423, M 470h

□ drive 12.5 = ½"

4558 72 • For commercial vehicles with EDC engines: MERCEDES-BENZ and MAN

With hole bored through to accommodate a connecting cable
 32 mm outside 6-point drive

4558-1

E.g. for MERCEDES-BENZ and MAN commercial vehicles
 With counterholder for fixation between compression nut and nozzle holder -

• 32 mm outside 6-point drive

4558-2 68 057344

125 1/2 32

4



4798-8/8, EAN-No. 4000896210749

Injector removal tool

- The 12 t hydraulic cylinder enables simplified loosening of very tight injectors
- Huge time saving since the engine does not have to be removed to disassemble the injectors
 For MERCEDES-BENZ Vito, CLK, Sprinter, Viano, Vario, 2.1 | · 2.2 | · 3.0 | V6 (CDI 2.1 | · 2.2 | Delphi, CDI 3.0 | V6 Bosch)

• In SmartCase (1/3) 165-L











798-13, EAN-No. 4000896**155248**

Hose clamp pliers

- For use in areas with restricted access where the clamp cannot be reached straight forwardly
- Application: For the operation of spring band hose clamps whose three ends fit tightly on the hose, e.g. on tank aeration lines and fuel lines
- Length: 192 mm
- Clamping range: 27 mm



798-5, EAN-No. 4000896031955

Hose clamp pliers

- Application: For spring band hose clamps
 Rotating jaws for areas with restricted access
- Length: 210 mm
- Clamping range: 6–40 mm





Made in Germany

1788 T-1, EAN-No. 4000896134304

Sliding hammer

- With coupler thread M10 (sliding weight 200 g)
 Together with injector extractor 4797-5





4797-5, EAN-No. 4000896**176137**

Injector extractor

- For disassembly of tight common rail injectors without removing the cylinder head

- For the simple removal of injectors together with sliding hammers, e.g. HAZET 1788 T-1, on MAN engines D08, D20, D26 and D28
 Especially suited to the very limited space in the cylinder head
 Due to the tool's special claw, the injector may be seized with caution, damage-free removal with the aid of the impact extractor
- Injector claw with inside thread M10 x 1.5 mm for easy insertion of the impact extractor





💳 Made in Germany

Can only be used in combination with 1788 T-1!

Taper key ejector

- For the safe and simple stripping of taper keys
- Suitable for quick stripping of taper keys out of the sprocket
- For the manual operation of input shafts on agricultural attachments











bent

125 1/2

2169-36, EAN-No. 4000896086566 Oil filter wrench

• ☐ drive 10 = 3/8"

NEW!

- Forged design
- Surface: chrome-plated
- For **MERCEDES-BENZ** van, Actros MP 1, MP 2
- For fuel filters **MAN** e.g. TGA







Made in Germany



2195, EAN-No. 4000896014101

2168-1, EAN-No. 4000896**223251**

For simple loosening and tightening with fitted 12.5 mm = ½" 4-point
 For e.g.: CLAAS Torion, LIEBHERR wheel loaders and wheel loaders with Euro 6 emission standard and LIEBHERR engines

Fuel filter wrench

Made in Germany

Cartridge wrench

- For loosening the granulates cartridges
- Forged design
- MAN No. 8099606-0307



2169-9, EAN-No. 4000896116690

Commercial vehicle oil filter wrench

- For the operation of oil filters e.g. from MANN and MAHLE/KNECHT
- For e.g.: Volvo, SCANIA, RENAULT, MAN, IVECO, FIAT, FODEN, IRISBUS, ASTRA, CATERPILLAR, LIEBHERR, JOHN DEERE, KOMATSU, FAUN, MITSUBISHI
- The torque value recommended by the vehicle manufacturer can be reliably achieved, e.g. with a HAZET torque wrench (Attention: observe the manufacturer's tightening torque values)

s 105 mm, 15-point HAZET 2169-9 GERMANY



Made in Germany

s **24 mm**

125 1/2



2168-46, EAN-No. 4000896**156252**



AdBlue® filter wrench MERCEDES-BENZ

- For the operation of the filter housing cap when replacing the **AdBlue® filter** (urea solution filter) on **MERCEDES-BENZ** commercial vehicles with BlueTec® engines e.g. Actros, Atego, Axor, Econic

 The tightening torque recommended by the vehicle manufacturer
- (please follow the instructions of the manufacturer) is reached e.g. with the torque wrench HAZET 6110-1 CT
- Forged design













10 3/8

- ☐ drive 10 = 3/8"
- For installing and removing oil filters and oil filter housing caps when changing
- For urea solution filter Ad-Blue® MAN e.g. TGX

s **32 mm, 6-point**



Made in Germany

BATTERY SERVICE | ELECTRICAL TESTING | VDE







5



Commercial vehicle system cable release tool assortment

- Guarantees damage-free release of the most common commercial vehicle contacts
- For damage-free release of flat plug contacts
- Malfunctions due to loose contacts can be remedied easily, quickly and professionally
 With sliding caps protecting the blades from damage and avoiding the risk of injury
- OEM quality "Made in Germany"





2152N/3, EAN-No. 4000896204151

Electronic set

- For troubleshooting on electronic components
- Measuring range 3-48 V
- Voltage display LED: 5, 12, 24, 48 V
 Polarity display: LED for positive or negative, AC voltage with illuminated LED
- Additional crocodile clip and probe tip for attaching
- Cable length: 1300 mm
- Probe tip, needle with sliding mechanism



1862, EAN-No. 4000896007301

Automatic wire stripper

- For PVC-insulated solid and flexible cables, conductor cross-section 0.5 up to 4 mm²
- Automatic adjustment to the conductor's cross-section, easy application
- Integrated diagonal cutter for wire cutting
- Length: 180 mm



4650-4, EAN-No. 4000896022038

Made in Germany

Battery pole and terminal brush

 Application: Cleaning the terminals and clamps

4650-3, EAN-No. 4000896**102051**

Special tool for battery plugs

- Special length allows universal application in areas with restricted access
- Application: For inserting and removing battery plugs • Profile is especially suitable for battery plugs
- Plastic T-handle
- Surface: chrome-plated
- Screwdriver width: 14.5 mm
- Screwdriver height: 1.7 mm





Made in Germany

1850 VDE

VDE combination pliers

• Induction-hardened cutting edges with grind

• Cutting edge hardness: 60 HRC

• EN/IEC 60900, DIN ISO 5746

• Surface: bright chrome-plated, with protective insulation

Made in Germany

H <u>AZET</u> No.	/ mm	EAN-No. 4000896+	
1850 VDE-22	160	007202	
1850 VDE-33	180	007219	
1850 VDE-44	200	007226	

1803 VDE

VDE diagonal cutter



Lap joint

• Induction-hardened cutting edges with grind

• Cutting edge hardness: 60 HRC • EN/IEC 60900, DIN ISO 5749

• Surface: bright chrome-plated, with protective insulation

Made in Germany

HAZET No.	/ mm	Rm N/mm² O 800	Rm N/mm² → 1600	EAN-No. 4000896+
1803 VDE-22	160	2.8	2.0	006137
1803 VDE-33	180	3.0	2.5	006144

1841 b VDE-33


EAN-No. 4000896**006441**



1000 V ₹

∰ <u>ØE</u> ▼

VDE snipe nose pliers



- Curved design (45°)
- Cutting edge hardness: 60 HRC
- Length: 200 mm
- EN/IEC 60900. DIN ISO 5745
- Surface: bright chrome-plated, with protective insulation









WORKSHOP TOOLS





LED folding light

- Small design for use in areas with restricted access
 5 pieces 0.65 W SMD LED, total power 3.25 W
- High-quality 2-component plastic housing with rubberised surface
 Flexible, 340° rotatable handle on the housing, lockable in 12 positions
 Fold-out and 360° rotatable hook (rear side)
- Incredibly powerful holding magnet with additional rubber lining on the underside of the housing
- Additional eyelet for attaching a retaining strap















LED Slim Light hand lamp• Display brightness on the back of the lamp enables optimal light adjustment

Additional top lamp for surface illumination

Power supply via Micro USB port





Top light







With magnet and hook. Freely adjustable via ball joint




















NEW!

1







2162-8, EAN-No. 4000896**213337**


Hand-operated dosing pump

The double scale enables precise dosing of various liquids
For hydraulic oils 50 mm²/s, synthetic oils 500 mm²/s, heating and diesel oils, water and emulsions or contaminated used oil
Coupler thread (hose/pipe) on the pump bottom: M15 x 1.5
Housing material: PVC
Hose inside ∅: 10 mm
Hose outside ∅: 16 mm

Hose outside Ø: 16 mm

NBR seals

• Suitable for diesel, water, oil and used oil




ENGINE | DIAGNOSIS | ENDOSCOPE TECHNOLOGY

Hose clamp pliers 798-15 B

- Operating self-gripping spring band and space-saving hose clamps on the cooling and heating system
- Particularly suitable for areas with severely restricted access where the direct application of usual pliers is not possible
- Plastic-coated, semi-flexible Bowden cable
- The Bowden cable enables working without a guiding hand
- Sliding guide device with integrated tension spring and adjustable reversible plate
- One-hand operation thanks to automatic toothed fixing device
- Handles with dip coating

HAZET No.	sb mm	/ mm	EAN-No. 4000896+
798-15 B	7-60	875	117727
Flexible hose for	or 798-15 B		
798-0150 B	-	-	142439
Bowden cable	for 798-15 A a	nd 798-15 B	
798-0152 A	-	-	097760
Sliding guide d	evice for 798-1	5 A and 798-1	5 B
798-0153 A	-	-	097784





4812N-10/3AF, EAN-No. 4000896219131

Video borescope with new swivelling probe

- Full 180° swivel enables e.g. a real reverse view onto valves in the cylinder
- Swivelling range: 1 x 180°
- Camera head only 11 mm long (-50 % compared to conventional designs), hence swivelling in the tightest space
- Bending radius only approx. 35 mm (-30 % compared to conventional designs)

- With light boost and integrated reflection reduction
 Luminous source: 4 dimming LEDs for optimum lighting
 4 x 90° image rotation at the press of a button (no need to turn the probe)
- Micro-lens: 4.5 mm \varnothing Front view with a resolution of 640 x 480 px
- Depth of field: 10 to 100 mm
- Casing made from steel mesh
- Metal connector between probe and housing
- Probe tip: IP 67
- Automatic power off to save energy
- Weight (net): 2.84 kg

• Contents:

- 1 m probe cable with 4.5 mm Ø micro-lens and LED luminous source
- 1 operating panel 1 SD card 4 GB
- 4 AA batteries










4812 N-1AS, EAN-No. 4000896187072 Flexible probe for video borescope Ø 6 mm • Depth of field: 10 to 60 mm • Ambient conditions: 0° to +55 °C Almolerit Conditions: 0 to 455 °C Bending range: 2 x 150°, Bending radius (approx.): 48 mm Probe tip may be fixed in position • Viewing direction of the camera: 90° (Side-View) no margins in view • Luminous source: 1 LED in 90° direction





Cushioned seat base Ø 320 mm

2 tool compartments

196-2, EAN-No. 4000896**149469**

Fender cover

- Made of specially coated anti-slip material
- Waterproof, oil and grease repellent
- Cover adheres almost completely vertically to all car body surfaces
- Fire safety complies with British and US Fed 302 standards
- Washable at 40°





195-2, EAN-No. 4000896125982

Mechanic's creeper

- For convenient working underneath a vehicle
- 6 castors (Ø 70 mm)











Creeper/pneumatic chair





Gloves • With micro-foam coating Breathable coating Maximum flexibility and freedom of movement

195-4, EAN-No. 4000896148707 **Pneumatic chair**

Loading capacity up to 150 kg
Tilt-resistant

• Provides a comfortable seat at the work area

Adjustable in height from 380 to 510 mm


360° rotation

LHAZET

1987 N-4, EAN-No. 4000896203840

- together with excellent mechanic protection
- Water repellent
- Material: 60 % cotton, 40 % polyester





www.hazet.de

PNEUMATIC TOOLS

Impact wrench

- Loosening torque (max.): 3400 Nm
- Extremely powerful tools
- Easy to use

9014 P-1

HAZET

9014 P-1

9014 PS-1

- Output designed with hole for pinning, as well as a nut-driver holder ring
- Lightweight and handy tool for attaining the highest torque values in commercial vehicle and industrial applications

-----586.7 mm --

2712

2712

3400

3400

· One-hand reversing switch

With extended spindle (240 mm) for optimal accessibility of wheel bolts

- · Operation optimised on both sides for left and right handed users
- Optimised feel

rpm

5500

5500

6.3

6.3

283

283

- · Air inlet possible on the handle at the bottom and rear
- Exhaust air is guided downwards through the handle
- Reduced vibrations
- Coupler plug: nominal size 10 mm (included)
- Forward/reverse: three-stage



Direct hammer striking mechanism: Fewer vibrations and higher output



HAZET

9013 M, EAN-No. 4000896212347

25 1"

25 1"

Impact wrench

- Loosening torque (max.): 1890 Nm • Exhaust air is guided downwards through the handle
- Reduced vibrations
- Forward/reverse: three-stage (forward), single-stage (reverse)
- Rotation speed :7300 rpm
- Weight (net): 2.1 kg
- Air requirement: 153 l/min (2.5 l/sec)

9012 M, EAN-No. 4000896188987

Impact wrench

• Sound power level (at working pressure): 93 db(A) Lp W





12.91(w) (7.2

9012 SPC, EAN-No. 4000896119639

- **Impact wrench**
- Loosening torque (max.): 850 Nm • Rotation speed: 7000 rpm
- Weight (net): 2.6 kg

125 1/2"

- Air requirement: 127.4 l/min (2.1 l/sec)
- Sound pressure level (at working pressure): 92.1 dB(A) Lp A
- Vibration acceleration: 7.42 m/s²



9013 MG, EAN-NO. 4000896109210

Impact wrench

- Loosening torque (max.): 1800 Nm
- Exhaust air is guided downwards through the handle • Forward/reverse: three-stage (forward), single-stage (reverse)

20 3/4"

- Magnesium housing
- Tightening torque (max.): 1627 Nm
- Recommended torque: 1084 Nm
- Air requirement: 198 I/min (3.3 I/sec) • Sound pressure level (at working pressure): 96.8 dB(A) Lp A
- Vibration acceleration: 12.18 m/s²
- Weight (net): 5.1 kg



9000-062, EAN-No. 4000896218936

Safety coupling for 20.95 mm (1/2")

- No risk of injury from hose impact
- Safe disconnection of the connection (unwanted disconnection is excluded) • Safety coupling depressurises the connection before decoupling
- One-hand operation

20 3/4"

125 1/2″

- Little effort during coupling and decoupling
- Omission of loud popping during coupling process





9000-080, EAN-No. 4000896214709



NEW!

Compressed air reducer

- Device for the reduction of working pressure to protect pneumatic equipment Can be ground into the compressed air line or connected directly to the pneumatic device
- For connecting motor-powered pneumatic devices with a working pressure of 6.3 bar
- Max. inlet pressure: 10 bar
- Outlet pressure: 6.3 bar
- Incl. air connection nipple for connection to compressed air coupling











PNEUMATIC | HAND TOOLS

125 1/2 20 3/4 4

215416

215409





Impact adapter

- With replaceable 123 1/2 plug-in blades
- For impact operation
- With borehole for locking pin or safety spring and groove for o-ring
- Proven with 990 S/11 and 985 S/11



985 S/11, EAN-No. 4000896211951

Impact screwdriver socket set

- 20 3/4 Drive allows transmission of high separation forces
- For screw connections on commercial vehicles e.g. on chassis, brake system (brake carriers), engines and shock
- Drive optionally with 129 ½, 24 mm or with adapter HAZET 1003 S-1
- With borehole for locking pin or
- safety spring and groove for o-ring • Sizes 14, 17 and 19 in short and long design





9040 Lg-3/2, EAN-No. 4000896206339

Air blow gun

1007 S-7/4

1003 S-07

- With 90° side nozzle and Venturi nozzle
- Application: For cleaning areas with restricted access on vehicles, machinery and agricultural machinery

Impact adapter

Replaceable plug-in blades 123 1/2

- Especially suitable for cleaning cooling fins
- Grip area with insulated lance to protect it from cold
- Increased efficiency due to Venturi nozzle (54 mm)
- 90° side nozzle (32 mm) enables cleaning of cooling fins
- Pressure (max.): 12 bar
- Ergonomic handle

Replaceable

- Coupler plug (incl.): 7.2 NW
- Hose diameter (recommended): 10 mm
- Working pressure: 6.3 bar
- Total length: 1085 mm
- Air requirement 450 I/min (7.5 I/sec)
- Weight (net): 0.31 kg



9035-5, EAN-No. 4000896132355

- **Needle scaler** • Adjustable needle cover
- Removes precise, small and large emerging patches of rust
- 19 needles (Ø 3 mm)
- 3200 impacts/min.
- Weight (net): 2.6 kg
- Air requirement: 170 l/min. (2.8 l/sec)
- Sound pressure level (at working pressure): 97 dB(A) Lp A
- Total length: 330 mm
- Vibration acceleration: 8.7 m/s²








Spare needles

- Suitable for needle scaler 9035-5
- 19 needles (Ø 3 mm)





Power: 420 Watts































• Contents:

- Multi sander for use with brush belts, strip wheels and foil erasers
- For removal of underbody protection, sealing compound, rust, corrosion, paint, plastic film, labels as well as for paint stripping
- Continuous speed regulation via speed regulator on back of handle
- Spindle size: 9 mm (hex)
- Delivery without accessories
- Power: 370 Watts • Rotation speed: 4000 rpm
- Working pressure: 6.3 bar • Air requirement: 102 l/min (1.7 l/sec)
- Sound pressure level (at working pressure): 79 dB(A) Lp A
- Vibration acceleration: 0.80 m/s² • Weight (net): 1.2 kg







Speed regulation

12.91(vi)


180° adjustable

handle









H <u>AZET</u> No.	Designation	4	EAN-No. 4000896+
9033-6-010	Adapter for brush belts 23 mm and foil erasers	-	213672
9033-6-01/5	Foil erasers (lighter version)	5	160167
9033-6-01A/5	Foil erasers (darker version) for water-based paints	5	160228
9033-6-02/5	Brush belt 23 mm wide, coarse and bent tips. For removing underbody protection, sealing putty, as well as paint stripping with rough sand-blasting effect	5	160174
9033-6-06/5	Brush belt 23 mm wide, fine and straight tips. For the removal of paint and rust, without sand-blasting effect	5	160211
9033-6-011	Adapter for brush belts 11 mm	-	213665
9033-6-03/5	Brush belt 11 mm wide, coarse and bent tips. For removing underbody protection, sealing compound as well as paint stripping with rough sand-blasting effect	5	160181
9033-6-05/5	Brush belt 11 mm wide, fine and straight tips. For removing paint and rust, without sand-blasting effect	5	160204
9033-6-041	Adapter for single strip wheels	-	213658
9033-6-040	Adapter for double strip wheels	-	213641
9033-6-04/5	Strip wheels	5	160198

9040 N-13, EAN-No. 4000896214648

Hose reel

- Hose stop function possible at any point with "Stop at any point"
- Neat winding of the hose thanks to automatic guidance
- Braked winding to prevent risk of accidents
- Suitable for compressed air or water
- Black hybrid polymer hose
- Temperature range: -40 to +80 °C
- Air inlet intake (from compressor/to machine): Outside thread 20.96 mm (1/2")
- Operating pressure (max.): 20 bar
- Weight (net): 9.5 kg



9040D-2.5, EAN-No. 4000896214631

Cable reel

- Line stop function possible at any point with "Stop at any point"
- Braked winding to prevent risk of accidents
- Including line circuit breaker
- For 230 V AC
- Only suitable for indoor use
- Temperature range: -20 to +45 °C
 Resilient when wound up: 1600 W
- Resilient when unwound: 3200 W • Weight (net): 9.2 kg








9042 N-1, EAN-No. 4000896176472

Grease gun, pneumatic

- Continuous pumping of grease · Gun-filling with grease cartridge,
- Air requirement: 230 I/min.








9043 N-10, EAN-No. 4000896198382

Switchable air blow and suction gun

- For sucking up dirt into the dust collection bag
- as well as for blowing surfaces clean
- With speedy one-hand switching of the function direction Well suited to cleaning truck cabs
- Vacuum level: 7.5 mm





Das Werkzeug

20 3/4"

NEW!



9233-010, EAN-No. 4000896218943

Cordless right-angle grinder 18 V

- High efficiency thanks to brushless motor
- Compatible with HAZET rechargeable batteries 9212-02 and 9212-05
- · Device stops if the speed drops sharply due to canting
- Motor stop 2 seconds after switch-off
- Constant speed even during difficult work
- · With safety lever
- Including 1 protective hood for cut-off wheels and grinding wheels
- Quick adjustment (without tools) of protective hood
- Spindle thread: M14
- Weight (with battery): 2.28 kg
- Weight (without battery): 1.53 kg
- Contents:

Cordless right-angle grinder, plastic case



Cordless drilling machine 18 V

- High efficiency thanks to brushless motor
- Compatible with HAZET rechargeable batteries 9212-02 and 9212-05
- Tool-free metal quick-clamping drill chuck 1-13 mm
- Selectable torque settings 15 + 1 drilling - stage 1: 0-560 rpm
- stage 2: 0-1900 rpm Robust machine housing
- Suitable for continuous operation
- Weight (with battery): 1.68 kg
- Weight (without battery): 1.27 kg
- Contents:

Cordless drilling machine, bag



9213-1000, EAN-No. 4000896222698

Cordless impact wrench 18 V, 5 Ah

- High efficiency thanks to brushless motor
- Compatible with HAZET rechargeable batteries 9212-02 and 9212-05
- Max. loosening torque: 1400 Nm

More power

20 3/4"

- Max. tightening torque: 1000 Nm
- Three selectable performance levels for the torque screw tightening: 1st level: approx. 180 Nm at 0-400 rpm
- 2nd level: approx. 400 Nm at 0-800 rpm
- 3rd level: approx. 1.000 Nm at 0–1800 rpm
- Forward/reverse: multistage
- · Lithium-Ion rechargeable battery
- Brushless DC motor (BLDC)
- Screw size: M24
- Contents:

Cordless impact wrench, plastic case





3-piece

1 or 2 batteries: The choice is yours!





Cordless right-angle

• Contents (3-piece set): 1 cordless right-angle grinder

1 Li-lon rechargeable battery

9233-7, EAN-No. 4000896**218325**

grinder set,

1 quick charger

18 V, 5.0 Ah

• In plastic case

3 pieces



Cordless drilling machine set, 3 pieces

- Contents (3-piece set): 1 cordless drilling machine 1 quick charger 1 Li-lon rechargeable battery
- 18 V, 2.0 Ah Supplied in bag



9213-1000/3, EAN-No. 4000896222704





wrench set, 3 pieces

- Contents (3-piece set): 1 cordless impact wrench 1 quick charger 1 Li-lon rechargeable battery 18 V, 5.0 Ah
- In plastic case



9233-7/4, EAN-No. 4000896**218950**

Cordless right-angle grinder set, 4 pieces

- Contents (4-piece set):
 cordless right-angle grinder 1 quick charger 2 Li-lon rechargeable batteries 18 V, 5.0 Ah
- In plastic case



9230-2/4, EAN-No. 4000896**218967**

Cordless drilling machine set, 4 pieces

- Contents (4-piece set): 1 cordless drilling machine quick charger 2 Li-lon rechargeable batteries 18 V, 2.0 Ah
- Supplied in bag



9213-1000/4,

Cordless impact wrench set, 4 pieces

- Contents (4-piece set):
 1 cordless impact wrench 1 quick charger 2 Li-lon rechargeable batteries
- 18 V, 5.0 Ah • In plastic case



9212-02 EAN-No. 4000896**213788**

Replacement battery 2.0 Ah





Replacement battery 5.0 Ah




9212-03

EAN-No. 4000896**204823**

Quick charger for rechargeable **batteries**



9233-010/5 EAN-No. 4000896219063





5



















TORQUE TECHNOLOGY









TORQUE TECHNOLOGY | SCREWDRIVER




















450 N

EAN-No. 4000896+

218417

Double open-end wrench

10.1

10.5

11.4

12.3

450 N-36 x 41

450 N-41 x 46

450 N-46 x 50

606

67.9

74.6

85.5

94.3



600 Lg-22

600 Lg-24

600 Lg-27

600 Lg-30

600 Lg-32

600 Lg-36

22

24

27

30

36

16.0

18.0

20.0

21.0

21.5

24.0

9.0

10.0

11.0

12.0

12.0

13.0

380

430

480

510

530

580

199525

198252

198269

199723

197675

205745




HAZET No

600 Lg/10

600 Lg/13







© s 10 · 11 · 12 · 13 · 14 · 15 16 · 17 · 18 · 19 mm

s 10 · 11 · 12 · 13 · 14 · 15 · 16 · 17 · 18 · 19 · 21 · 22 ·







81.1

94.4


102.2

396.7

439.5

498.0

020652





Q 🛂





2115-T/13 P

EAN-No. 4000896**012107**

T40 · T45 · T50 · T55 · T60

2115 · **O**

Offset screwdriver set

T7 · T8 · T9 · T10 · T15 · T25 · T27 · T30

O 👨

2100/10 P

EAN-No. 4000896**011506**

Metric dimensions 2100 · O


Offset screwdriver set

 $2 \cdot 3 \cdot 4 \cdot 5 \cdot 6 \cdot 7 \cdot 8 \cdot 9 \cdot 10 \cdot 12 \text{ mm}$






1116 · 25 1









GENERAL WORKSHOP EQUIPMENT





167 XXL, EAN-No. 4000896210565

Assembly trolley XXL Assistent®

- Flexible and stable for all purposes
- With an intermediary tray as standard
- Intermediary tray: Adjustable in 12 height positions in 38 mm steps in order to easily set aside spare parts and workpieces, for example
- More intermediary trays are optionally available
- Worktop: wood multiplex birch, replaceable
- Face-side perforated tool panels for attaching accessories
- Robust sheet-steel design
- Loading capacity working top 300 kg, intermediate tray 50 kg, ground compartment 80 kg

- Large ball-bearing wheels (Ø 125 mm)
 2 swivel castors Ø 125 mm (2 x with dual brake), 2 fixed castors
 With thread guard protects the bearings against dirt and threads
 Easy manoeuvrability, even with bigh dynamic load
- Grey non-marking elastic tyres enable smooth movement
- Sturdy handle, firmly attached to the trolley

- 1245,5mm

370,5 mi

370,5mm

• Maximum loading capacity (dynamic): 500 kg





500 kg



 $h \times w \times d$: 1002 x 1245 x 585.5 mm





Made in Germany



167-3, EAN-No. 4000896**205332**

Service trolley Assistent

- Flexible and stable for all purposes
- Centre layer adjustable in 15 heights creates space for e.g. canisters
- More layers and anti-slipping mats (2 x 180-38) are optionally available
 Robust sheet-steel design, loading capacity per layer: 50 kg
 Large ball-bearing wheels (Ø 100 mm), 2 swivel castors (1 x with dual brake), 2 fixed castors

inlays per layer

- With thread guard protects the bearings against dirt and threads
 Easy manoeuvrability, even with high dynamic load
- Grey non-marking elastic tyres enable smooth movement
- Sturdy handle, firmly attached to the trolley
- Suitable for HAZET Safety-Insert-System, 2-component soft foam insert
- Loading capacity (per layer): 50 kg

890 mm

275 mm





Adjustable in 15 heights

Intermediary tray adjustable in

12 positions (steps: 38 mm)

3 x 50 kg



h x w x d: 843 x 890 x 542 mm



2 x 3/3+/layer



Made in Germany


29

167 T, EAN-No. 4000896**210503**

- Multi table Assistent® With sturdy impact protection on all important struts for protecting
- important areas, e.g. body and high quality rims
- Table can be collapsed downwards by 90°
- Adjustable in 15 height positions (steps: 25 mm) Robust welded design
- Ball-bearing-mounted wheels (Ø 50 mm)
- 4 swivel castors, 2 castors with brake • Easy manoeuvrability, even with high dynamic load
- Grey non-marking elastic tyres enable smooth movement • Fits under vehicles with a ground clearance greater than 130 mm
- Loading capacity of table: 35 kg
- Maximum loading capacity (dynamic): 150 kg
- Delivery, flatly packed (H x W x D approx.): 110 x 930 x 780 mm











Here is your personal assistant







Design your trolley how you like!

Your perfect organisation system for your tool trolley. Snugly embedding for all your tools.

Endless combination options mean you can arrange your trolley according to your needs.

You can find more inserts at: www.hazet.de







2/3

3/3

Made in Germany












• 900 (a) 122 1/2 10-27; 916 SP 122 1/2; 917-5 122 1/2 124 1/2; 918-10 122 1/2 124 1/2; 920 124 1/2 1/2 1/2











163-210/19, EAN-No. 4000896164714 **Combination wrench set**


• 19-piece 2 s 8 – 34 mm





TOOL TROLLEYS







163-517/15, EAN-No. 4000896218745


Electronic screwdriver set



163-385/12, EAN-No. 4000896196944

Ratcheting combination wrench set

• 12-piece 🖘 **3 − 19 mm 3 − 19 mm**





163-297/26, EAN-No. 4000896186242

Screwdriver set

• 26-piece **○ ○ ○** ○



163-520/15, EAN-No. 4000896218677

Double box-end wrench set




Made in Germany



163-211/20, EAN-No. 4000896164707

Wrench / socket set

• 20-piece 5 s 8 x 9 – 34 x 36 mm; **○** T60, T80, T100; **○** *s* 14, 17, 19, 22 mm





163-257/4,

Pliers set

• 4-piece




163-299/8, EAN-No. 4000896186723

Drift pin set

• ==== s3-6 mm; =








163-518/9, EAN-No. 4000896218707

Double box-end wrench set



Made in Germany













Tool trolley or workbench: Your decision!














0-179/244, EAN-No. 4000896204236 Tool assortment, individual • 244 expert tools









2 Socket set 163-181/17, 17-piece 10 3 s 10−22 mm

3 Combination wrench set 163-210/19, 19-piece

≕0 **s** 8−34 mm **4** Tool set 163-211/20, 20-piece

s 8 x 9–34 x 36 mm **○** T60, T80, T100 **○** *s* 14, 17, 19, 22 mm

6 Double box-end wrench set 163-296/7, 7-piece *₱ s* 6 x 7–21 x 22 mm

6 Screwdriver set 163-297/26, 26-piece 0000

Ratcheting combination wrench set 163-385/12,

≕ s 8−19 mm Screwdriver socket set

163-407/35, 35-piece $\footnote{10}{192}$ \foot

Pliers set 163-257/4, 4-piece

TORX® Screwdriver set 163-380/4, 4-piece **O** T15–T30

Socket set 163-382/3, 3-piece ● s 8, 10, 13 mm

TORX® Screwdriver set 163-182/9, 9-piece

O T6–T30 Universal set 163-372/25, 25-piece

Soft foam insert with compartment for small pieces

6 Soft foam insert with compartments for small pieces

NKW19/EN/XX/0/I. 02.19/PDF

