

SPECIAL WORLDWIDE

2024/
2025



Das Werkzeug

New Products and Specials



 **Made in Germany**

EISENaward
2024



WINNER




Assistant® 176N-7 Made in Germany

NEW!

- ▶ **High flexibility**
 - Handle and castors can be mounted either on the left or right
- ▶ **New practical HAZET design**
 - Handle strips for a comfortable feel
 - Newly designed modern plastic cover with textures and large recessed, fully usable work surface
 - Bevelled edges prevent damage
- ▶ **Numerous fixing options**
 - Additional accessories, e.g. HAZET paper bin, can holder mountable on left and right side
 - Additional rear screw-on points for mounting further accessories
- ▶ **Two-level locking concept**
 - Central locking, cylinder lock and two folding keys
 - Mutual drawer locking for minimum tilting risk




Made in Germany
176N-7
EAN-No. 4000896264681



Handle can be mounted on the left or right

Incl. handle strips

Bevelled edges



Delivery without accessories

Optionally extendable with accessories

HAZET No.	Designation	
176N-26	Perforated tool panel for 176N-7	NEW!
176N-261	Mounting rail for perforated tool panel	NEW!
161T-176N/4	Set of separation sheets for flat drawers	NEW!
161T-176N/4H	Set of separation sheets for high drawers	NEW!
179N-33	Paper bin incl. holder	
161N-3D/2	Cable drum incl. holder	
179N-45	Tablet holder	
179N-35	Can holder, for at least 4 cans	
180-34	Holder for paper reel	
180-24	Document holder	
179N-46	Impact wrench holder	

Set of separation sheets for flat and high drawers



Slot / Phillips set with holder

- Screwdriver holder for wall mounting




HAZET No.	Designation	EAN-No. 4000896 +
811SH	Screwdriver holder	264582



NEW!



811SH-1/7
EAN-No. 4000896264605



HAZET No.		Blade mm	l_1 mm	l_2 mm
811-PH1	+	PH1	80	185
811-PH2	+	PH2	100	215
811-30	●	0.5x3	80	165
811-40	●	0.8x4	100	185
811-55	●	1.0x5.5	125	230
811-65	●	1.2x6.5	150	265

Beam/plate puller

- The use of wood screws results in only minor processing marks
- Suitable for wood types with increased risk of cracking and splitting
- Tensioning, pulling, pressing of timbers
- Suitable for hard-to-reach places (e.g. in angled areas such as sloping roofs etc.)
- Pulling together of corner joints possible
- Aluminium plates to prevent discolouration
- Simple and ergonomic handling thanks to reversible ratchet
- Smooth running acme thread TR 16 x 5
- 6 boreholes a 8.5 mm \varnothing per aluminium plate
- Span: 115 mm
- Overall width: 581 mm
- Total height: 280 mm
- Aluminium plate size: 150 x 75 mm
- Number of aluminium plates: 2




NEW!

Available from October 2024

Made in Germany
1774-2
EAN-No. 4000896264445

Avoids the risk of cracks and splits



PRECISION THAT INSPIRES: 1/4" TORQUE SCREWDRIVERS FOR BITS

- ▶ High precision and accuracy
- ▶ Unique torque screwdriver for bits on the market with **slip clutch (slipper)** in 36° steps and **free-running ratchet**, e.g. for use in confined installation spaces
- ▶ Large torque range: **0.2 – 10 Nm**
- ▶ Release accuracy tolerance: **±6%** of the set value
- ▶ Release mechanism made of high-alloy tool steel with excellent wear resistance for long service life
- ▶ Developed and produced by HAZET
- ▶ DIN EN ISO 6789-2:2017

6.3 1/4"

NEW!



EISENaward
2024



WINNER



Made in Germany



Excellent readability




Excellent readability of the torque setting thanks to large, clear numerical display

Freewheel ratchet



"Ratchet function" with freewheel mechanism, with right ▶ | left ◀ | fixed ■ | switching enables fast work thanks to smooth re-gripping



Slip clutch

Safe use due to the clutch slipping over at the set value



36°

Short ergonomic release distance thanks to the fine graduation of the slip clutch when loosening and tightening screw connections in confined installation spaces

Release distance that is easy to feel with clearly audible signal

Quick changer



6.3 1/4"

1/4" inside hexagon bit holder with convenient quick-release fastener: Quick bit change with one hand

NEW!

Lock and latch



Easily recognisable locking status thanks to lock symbols

Sustainability

thanks to recalibration and repair



Our torque screwdrivers for bits have a long service life, can be recalibrated and repaired if necessary thanks to our good supply of spare parts!

Thinking ahead, our engineers took this into account during the development phase.

Every day, our tools repair many everyday objects that otherwise would often be irreparably destroyed. We call this "double sustainability".



SYSTEM 6004CT with standard handle

- Release accuracy tolerance: $\pm 6\%$ of the set value



- 0.2 – 1.2 Nm

Made in Germany

6004CT-12

EAN-No. 4000896260041



SYSTEM 6005CT with sliding T-handle for high torques

- Better power transmission thanks to ergonomic T-handle
- Release accuracy tolerance: $\pm 6\%$ of the set value



- 4 – 10 Nm

Made in Germany

6005CT-100

EAN-No. 4000896260089



Nozzle set

- Extension of the application ranges of the 2-way air blow gun 9040-4 and the long air blow gun 9040LG-3/2
- Wide range of applications thanks to various nozzle designs
- Connection (outside thread): 1/8" PF 28

Contents:

- ① Long rubber nozzle 63 mm (scratch protection)
- ② Short rubber nozzle 13 mm (scratch protection)
- ③ Plastic surface nozzle (surface cleaning)
- ④ Metal nozzle with spherical air outlet (non-blocking)
- ⑤ Metal nozzle with safety function (non-blocking)



9040-43/5

EAN-No. 4000896263646



5

NEW!

2-way air blow gun cone set

- For blowing out pipes, boreholes, etc. to form a seal
- Compressed air cleaning of clogged or dirty lines/hoses, e.g. fuel, air conditioning and AdBlue® lines, hydraulic lines as well as windscreen washer system and coolant
- Adaptable to 2-way air blow gun 9040-4 and 9040LG-3/2 (long version)
- Loosening stuck ignition coil plugs (pneumatic inflation)
- Removal of pencil coils e.g. on 1.0 l · 1.0 l TSI · TFSI · TGI · GTI · CNG · 1.2 l TSI · 1.4 l-25 · 30 · 35 · 40 · 45 TSI · TFSI · TGI · CNG · GTE · Mild Hybrid · e-Hybrid-1.6l · 1.6 l SRE · MPI 2.0 l GTI engines
- **AUDI** A1 · A3 · A4 · A5 · Q2 · Q3
- **CUPRA** Formentor · León
- **SEAT** Alhambra · Arona · Ateca · Ibiza · León · Mii · Tarraco · Toledo
- **ŠKODA** Citigo · Fabia · Kamiq · Karoq · Kodiaq · Octavia · Rapid · Scala · Super · Yeti
- **VW** Caddy · Golf 6, 7, 8 · Jetta 4 → 7 · CC · Passat B8 · Polo 5, 6 · Arteon · Beetle · Taigo · Tiguan · Touran · T-Cross · T-Roc · Up! · Scirocco · Sharan · T7
- Coupler thread: 1/8" PF 28

Contents:


- ① Stainless steel extension 187 mm (9040-41)
- ② Air blow gun with long nozzle
- ③ Short nozzle

Set of cone nozzles, 3-piece (9040-42/3):

- ④ Cone nozzle Ø 13 mm
- ⑤ Cone nozzle Ø 35 mm
- ⑥ Cone nozzle Ø 25 mm

6

NEW!



9040-4/6

EAN-No. 4000896263660



Compressed air hose Ø 10 mm

- Professional use on compressed air tools in industry, workshops or for DIY work
- Compressed air hose with quick coupling and connecting nipple (7.2 mm)
- Grouted coupler bushing / coupler plug included
- PVC-NBR hybrid polymer compressed air hose
- In accordance with DIN EN ISO 5774
- Working pressure: up to 20 bar
- Burst pressure: 60 bar
- Air inlet intake: coupler bushing 7.2 mm type 1
- Air inlet intake: coupler plug 7.2 mm type 1



Total length: 10 m

9040N-1010

EAN-No. 4000896263684



Total length: 20 m

9040N-1020

EAN-No. 4000896263707



Incl. kink protection on both sides

Accidental hazards are avoided thanks to conspicuous visibility in HAZET light blue

NEW!

NEW!

Pneumatic chair

- 5 low-noise, smooth-running castors with multiple bearings \varnothing 75 mm
- Large, extra thick cushion \varnothing 350 mm
- Easy to clean
- Capacity: dynamic capacity up to 150 kg
- Can be adjusted in height by hand: 430 – 550 mm
- Tool storage with practically divided compartments
- Provides a comfortable seat at the work area
- Pneumatically adjustable in height
- Tilt-resistant



Particularly stable design thanks to square tubular frame




195N-4
EAN-No. 4000896261949



Measuring cup

- For brake fluid, battery fluid and non-acidic liquids
- Material: HDPE
- Colour: white / transparent

NEW!



Incl. lid!



2 l
198-5

EAN-No. 4000896174478



5 l
198-6

EAN-No. 4000896174522



5 l
198-8

EAN-No. 4000896174508



HAZET THERMAL CAMERA – FOR THE BEST POSSIBLE VIEW!

- ▶ Improved resolution
- ▶ Fascinating technology
- ▶ Easy-to-handle design



Thermal camera

- Building diagnostics, electrical installation, sanitary, air-conditioning and heating technology as well as inspection of engine compartment, brake system, cooling and heating system
- Automatic hot, cold and central point measurement
- Screen size: 2.4 inch LCD screen
- Display resolution is: 320 x 240 pixels
- Thermal (or Enhanced IR) resolution: 160 x 120 pixels
- Battery life: up to 8 hours
- Storage medium: Micro SD card (included in delivery) up to 150,000 images
- Image sensor: Vanadium oxide uncooled focal plane arrays (FPA)
- Refresh rate: 25 Hz
- Thermal sensitivity (Noise Equivalent Temperature Difference, NETD): <math>< 40 \text{ mK } (0.04^\circ \text{ C})</math>
- Measuring accuracy maximum ($\pm 2^\circ \text{ C } \cdot \pm 2\%$):
Ambient temperatures $15^\circ \text{ C } - 35^\circ \text{ C}$ / Object temperatures above 0° C
- Field of view: $50^\circ \times 50^\circ$
- Temperature range: $-20^\circ \text{ C } - 550^\circ \text{ C}$
- Protection rating: IP54
- SD card (4 GB) included
- Dimensions (H x W x D): 196 x 117 x 59 mm
- Weight: 290 g

NEW!



Laser pointer for targeting



Power supply: USB-C cable (Micro USB)



Photo	+	Thermal object image	=	Fusion

Including hand strap




Better resolution

Additional camera for better resolution of live video recordings (640 x 480 pixels)




6 colour palettes for optimum diagnostics

6 colour palettes: Black Hot · White Hot · Rainbow · Ironbow · Fusion · Red



Field of view: 50° x 50°

Enlarged field of view



More info



1992N-1
EAN-No. 4000896263523



HAZET VIDEO BORESCOPE WITH HD CAMERA – WITH A HIGH LEVEL OF DETAIL!




- ▶ Bright and sharper image
- ▶ Better details
- ▶ Clearer image



HD video borescope set with 360° swivelling probe Ø 3.9 mm

- Wired connection of a smartphone as a display (Lightning / USB-C)
- Additional magnification of the image possible using the smartphone display (drag)
- Image memory dependent on smartphone memory
- Robust, swivelling and adjustable smartphone holder (span: 58 – 100 mm)
- With temperature warning alarm (app) and automatic switch-off if the maximum permissible camera temperature is exceeded
- Photo and video recording via app or control via operating elements of the borescope
- Joystick control of the camera probe on the basic unit
- Focus range (DOF): 5 – 100 mm
- Viewing angle (FOV): 100°



NEW!

Your own smartphone as a display!

Removable Li-Ion battery (1 x type 18650) without additional tools

Fully articulating probe with Ø 3.9 mm

5-piece set in protective soft case with moulded insert:

- Basic unit and HD probe
- Data cable USB-A to Lightning (IOS), length: 0.3 m
- Data cable USB-A to USB-C (Android, current IOS etc.), length: 0.3 m
- Data cable USB-A to USB Micro (Android etc.), length: 0.3 m
- Charging cable USB-A to USB-C, length: 1.0 m



Your own smartphone as a display!

Joystick control

Joystick and control via operating elements

Smartphone holder (58 – 100 mm)



4812-24/4AF	
Camera probe	Ø 3.9 mm articulating probe with front camera (Axial 180°, Radial 360°)
Display	Depending on the smartphone
Zoom	Zoom: 5x (with display of the zoom factor in the app)
Display resolution	Depending on the smartphone connected
Brightness setting	3-level
Energy source	Removable Li-Ion battery (1 x type 18650) without additional tools
Image format (jpg)	960 x 720 / 1280 x 720 pixels
Video format (MP4)	960 x 720 / 1280 x 720 pixels
Data transfer	USB-C
IP protection rating	IP54 (basic unit) IP67 (probe)
Handling	With handle and sturdy smartphone holder
Tripod thread	✓
Mirroring of the camera image	–
Negative representation	–
Connectivity	USB to USB-C / USB to Lightning
Smartphone App Android / IOS	✓
Weight of device without battery and smartphone	0.38 kg
Weight of device with bag and cable set	1 kg
Dimensions (L x W x H)	220 x 78 x 50 mm

More info




4812-24/4AF

EAN-No. 4000896264568



NEW FEATURES FOR OUR POWER ADAPTER!

- ▶ For all sockets with outside hexagon s 24 mm
- ▶ **2-in-1:** One socket for two applications (1/2" · 3/4")



1/2", 24 mm impact socket set, inside TORX®

- **Screw connections on commercial vehicles, passenger cars and vans with TORX® profile, e.g. on the chassis or brakes**
- Operation with various drive tools possible:
 - 1/2" ratchet or impact wrench
 - s 24 mm socket and box-end wrench or open-end wrench
 - Adapter 1003S-1 enables drive in 3/4", e.g. with HAZET 3/4" impact wrench 9013TT
- 995S6-T50Lg operation of the screw connection on the steering knuckle when changing the brake discs / wheel bearings on **FORD** Transit model year 2006 →
- Optionally available adapter 1003S-1 for 3/4" (20 mm) drive
- Drive design: With borehole for locking pin or safety spring and groove for o-ring
- Output: Inside TORX® profile
- Wrench sizes: T40, T45, T50
- Manual / machine operation: For impact operation
- Surface: Black phosphatized, oiled

6-piece set:

- 3 short sockets (43 mm): 995S6-T40 · 995S6-T45 · 995S6-T50
- 3 long sockets (75 mm): 995S6-T40Lg · 995S6-T45Lg · 995S6-T50Lg


NEW!



Made in Germany
995S6/6
 EAN-No. 4000896264780

1/2", 24 mm impact sockets, inside TORX®



Made in Germany


HAZET No.	S	l_1 mm	l_2 mm	d mm	EAN-No. 4000896+
995S6-T40	T40	11	43	24	263202
995S6-T45	T45	11	43	24	263226
995S6-T50	T50	13	43	24	263240
995S6-T40Lg	T40	43	75	24	263288
995S6-T45Lg	T45	43	75	24	263301
995S6-T50Lg	T50	45	75	24	263264


NEW!



1/2" · 3/4", 24 mm impact socket set

- Screw connections on commercial vehicles, passenger cars and vans with TORX® profile, e.g. on the chassis, brakes, wheel screw connections
- Operation with various drive tools possible:
 - 1/2" ratchet or impact wrench
 - s 24 mm socket and box-end wrench, open-end wrench or ratcheting combination wrench
 - Adapter 1003S-1 enables drive in 3/4", e.g. with HAZET 3/4" impact wrench 9013TT
- Choice of drive 1/2" (12.5 mm) or s 24 mm or 3/4" (20 mm)
- Unlimited combination options
- Drive design: With borehole for locking pin or safety spring and groove for o-ring
- For HAZET *Assistent*® with a drawer depth of 398 mm: 173 · 179 · 179N · 179NX · 179W · 179NW · 179BIG-1 · 179XL · 179NXL · 179XXL · 179NXXL · 179AXXL · 179TXXL · 180



NEW!

2/3+			
------	--	--	--



Contents:

- 1003S-1 · 1003S-07 · 1000S-G1736 · 1000S-H1736
- 990S-12, -12Lg, -14, -14Lg, -16, -16Lg, -18, -18Lg
- 985S-14, -14Lg, -17, -17Lg, -19, -19Lg, -22, -24
- 900SZ6-19, -21, -22, -24, -27, -30, -32, -36
- 995S6-T40, -T40Lg, -T45, -T45Lg, -T50, -T50Lg
- 903SLg6-17 · 6-19 · 6-21
- 900SLg6-24



Made in Germany

163-612/40

EAN-No. 4000896264704



1/2", 24 mm outside hexagon impact screwdriver socket set, internal serration XZN


- Operation with various drive tools possible:
 - 1/2" ratchet or impact wrench
 - s 24 mm socket and box-end wrench or open-end wrench
 - Adapter 1003S-1 enables drive in 3/4", e.g. with HAZET 3/4" impact wrench 9013TT
- Screw connections on commercial vehicles, passenger cars and vans with XZN profile, e.g. on the chassis
- **MERCEDES-BENZ C-Class W204 (2007-2015) wishbone screw connection**
- **VW / AUDI wheel bearing housing screw connection**
- Drive design: With borehole for locking pin or safety spring and groove for o-ring
- Wrench size: M12
- Surface: Black phosphatized, oiled

2-piece set:

- 1x 990S-12 (short, 43 mm)
- 1x 990S-12Lg (long, 75 mm)


NEW!

1/2" S 24 mm



l_1 mm	l_2 mm	d mm
5	43	24

 Short design
 M12

990S-12



990S-12Lg



l_1 mm	l_2 mm	d mm
39.7	75	24

 Long design
 M12

Made in Germany
990S-12/2
 EAN-No. 4000896264667

1/2", 24 mm outside hexagon traction profile, impact socket set

- Operation with various drive tools possible:
 - 1/2" ratchet or impact wrench
 - s 24 mm socket and box-end wrench or open-end wrench
 - Adapter 1003S-1 enables drive in 3/4", e.g. with HAZET 3/4" impact wrench 9013TT
- **Double protection: Easy-to-rotate external plastic sleeve (replaceable) to protect the rims when screwing wheel bolts. Plus: Internal plastic insert to protect the surface of wheel bolts**
- Especially for vans and light trucks but also suitable for passenger cars
- Colour-coded plastic sleeves (blue, yellow, red) facilitates finding the correct size
- With borehole for locking pin or safety spring and groove for o-ring

3-piece set:

- 903SLg6-17
- 903SLg6-19
- 903SLg6-21


NEW!

1/2" S 24 mm



s 17 mm



s 19 mm

Made in Germany

HAZET No.	S mm	l mm	EAN-No. 4000896+
903SLg6-17	17	87	223596
903SLg6-19	19	87	223589
903SLg6-21	21	87	262960

NEW!


s 21 mm

Made in Germany
903SLg6/3
 EAN-No. 4000896264643

Brake piston readjusting tool for 1-piston and multi-piston brake callipers

- 2-in-1 device for 1-piston and multi-piston brake callipers
- Damage-free readjusting brake pistons (floating callipers / fixed callipers) on disc brakes
- Suitable for 1-, 2- and 4-piston brake callipers
- Can also be used with 6-piston brake callipers thanks to optionally available brake piston readjusting tool adapter plates 4971-3/2
- Fast and uniform readjusting without tilting
- For common vehicle types without integrated locking device for handbrakes
- Plate width: 50 and 100 mm
- Working range: 15 – 90 mm
- Avoids damage to boots and pistons
- High accuracy as well as high stability allow continuous use
- Less force expended thanks to exact guiding
- Plate size: 94 x 50 x 12 mm
- Plate size: 94 x 100 x 12 mm

NEW!



Made in Germany
4971-4
 EAN-No. 4000896262922



Brake piston readjusting tool adapter plate set for 6-piston brake callipers

- Easy adaptation using magnet on brake piston reset tool 4971-1 and 4971-4
- For brake piston readjusting tool 4971-1 and 4971-4 for damage-free resetting of 6-piston brake callipers
- Extension of width of contact surface to 165 x 72 mm
- Easy fixing of the adapter plates with 1 disc magnet: Ø 20 mm
- Plate size: 165 x 70 x 6 mm
- Surface: galvanised
- Magnet size: Ø 20 mm
- Magnet pull-off force: 2 kg

2 NEW!



Made in Germany
4971-3/2
 EAN-No. 4000896262908



3/8" brake calliper screwdriver socket, outside hexagon, s 6 mm

- Screwdriver socket adapted to limited space conditions for easy use of operating tools
- Operation of the guide bolts s 6 at the rear brake callipers of the **MERCEDES-BENZ** V-Class
- Use torque wrench with 3/8" (10 mm) drive, e.g. HAZET 6110-1CT or 5110-3CT for controlled screw tightening (observe manufacturer's instructions)
- With fixed blade (s 6 mm) for inside hexagon screws
- For manual operation

NEW!


10 3/8



Made in Germany

2784-2

EAN-No. 4000896263721



l_1 mm	l_2 mm	d mm	s mm
6	23	17	6

 Further sizes in the HAZET programme: Information and price at www.hazet.de

Made in Germany

HAZET No.	l_1 mm	l_2 mm	d mm	s mm	Brake calliper screwdriver socket	EAN-No. 4000896+
2584-8	6.6	24	19	8	For AUDI TT model year 2007 →, A4 model year 2001 → A6 model year 2005 →, A8 model year 2003 →	149438
2784-1	6.6	24	19	7	For MERCEDES-BENZ Type 204 (C-Class)	148530

3/8" injection line wrench set

- Very narrow diameter s 17 mm only \varnothing 23 mm, s 18 mm only \varnothing 24.4 mm
- Operation of the union nut on high-pressure line on the injection valve of the common rail injection system
- Proper operation of the injection line screw connection
- For fuel lines on **MERCEDES-BENZ** · **VW** · **AUDI** · **SEAT** · **ŠKODA** · **BMW** vehicles
- Also suitable for operating other cable glands with s 17 or s 18 mm
- The tightening torque required by the manufacturer is achieved by using a HAZET torque wrench (observe manufacturer specifications)
- Slim design
- For manual operation
- Slot width: 8 mm
- Surface: chrome-plated

2

NEW!

10 3/8



s 17 mm

s 18 mm

Contents:


- 4550-17, s 17 mm
- 4550-18, s 18 mm

s 17 mm



10 3/8

s 18 mm



10 3/8

Made in Germany

4550-17/18/2

EAN-No. 4000896264308

3/8" releasing tool for cover of coolant expansion tank, VAG

- Optimised design of the releasing tool for very special installation conditions of the coolant expansion tank on the **VW** ID.Buzz from model year 2022, which is difficult to reach in its installation position in the front area
- Problem-free loosening of very tight covers on the **VAG** coolant expansion tank
- Exact fit of releasing tool avoids damage to the cover
- For **VW** and Group vehicles as well as electric and hybrid models (MQB platform model year 2013→)
- Manual operation is only possible with great difficulty due to the geometric shape / low overall height of the cover and the recessed seat in the expansion tank
- Outside diameter: 92 mm
- Height: 35 mm
- For manual operation

NEW!

10 3/8



Narrow outer diameter and angled bracket



Made in Germany

4803-2

EAN-No. 4000896262885



Mini battery cell tester with QR code function

- Simple test of the starting capacity and condition of vehicle batteries and the starting and charging system
- Transfer of results to smartphone / tablet
- For 12 V systems in passenger cars, commercial vehicles and motorcycles as well as 12 V batteries
- 4 membrane keys
- Robust pole terminals with insulated handles
- Large, backlit LCD display
- Tests and detects defective cells in all types of starting batteries, including lead-acid batteries, AGM flat batteries, AGM spiral batteries, GEL batteries, start/stop batteries and rechargeable LI-ION batteries
- Device does not require its own battery and guarantees constant operational readiness
- Analysis of batteries in accordance with most battery standards, such as CGA, BCI, CA, MCA, DIN, IEC, EN, SAE, GB
- Reverse polarity protection to protect the device, vehicle and battery
- Large lithium battery working range, e.g. according to CCA standard 20 – 1000 A
- Large lead-acid battery working range, e.g. according to CCA standard 100 – 2000 A
- Possibility of individualising the test results shared by QR code (number plate, repair workshop, tester, test date)

4650-6

EAN-No. 4000896264629



	4650-6
Lithium compatible	✓
Storage temperature	-20 to 70° C (-4 to 158° F)
Operating temperature	0 to 50° C (32 to 122° F)
Weight	200 g
Dimensions (L x W x H)	80 x 80 x 22 mm



TESTBERICHT

BATTERIETE

ST

GEL BATTERIE

SPANNUNG: 12.39 V

AUSWAHL INPUT: DIN

NENNWERT: 900 A

TESTWERT: 259 A

INNENWIDER R: 5.07 mΩ

WECHSELBATTERIE

GESUND: ●

LADUNG: 41%

START TEST

START: NORMAL

SPANNUNG: 10 V

UHRZEIT: 500 ms

LADE TEST

LADE:	SPANNUNG NORMAL
LADETEST:	14.15 V
LEERLAUF:	14.4 V
WELLEIGKEITS:	10 mV

NEW!

Battery test

Starter test

Alternator test

Generation of QR codes for sharing the test results on a smartphone/tablet



Operating tool for fixing nut on spring strut, MERCEDES-BENZ

- Optimally matched operating tool (space conditions, loosening and tightening torques). Pay attention to the vehicle manufacturer's specifications
- Operation of the fixing nut for the spring strut on the **MERCEDES-BENZ** Sprinter Type 910 (with front-wheel drive) from model year 2018 → and E-Sprinter from model year 2020 →
- Output: ≤ 106 mm
- Outside diameter: 151 mm
- Height: 49 mm

12⁹ 1/2

NEW!



Made in Germany

2710-105

EAN-No. 4000896262946



NEW!

NEW TOOL TROLLEY 176N-7 WITH 193 EXPERT TOOLS



Das Werkzeug

Assistent[®]


Made in Germany



3/3	
-----	--

- ▶ Incl. new inserts: 163-613/152 / 163-614/16
- ▶ Mini reversible ratchet for bits 863MB
- ▶ SmartCase 2200SC-3
- ▶ New screwdriver series 811
- ▶ Universal pliers 760-26

163-30/25 s 6 – 24 mm s 6x7 – 21x22 mm



NEW!

193 176N-7/193
EAN-No. 4000896264810

NEW!


HAZET SMART CASE

HiPer

163-614/16 811 0.5 x 3.0 – 1.2 x 6.5 mm 811 PH 1, PH 2 811 T10 – T30




163-613/152 83 1/4 128 1/2 63 1/4 22 1/2 s 10 – 32 mm 63 1/4 s 4 – 13 mm



Your HAZET specialist dealer

Incl. new screwdriver series 811

Universal pliers 760-26



4 000896 265367
 SSW2425/EN/XX/0 1 08.24/2.25/UK/MD
 Copyright 2024 ©
 HAZET-WERK Hermann Zerver GmbH & Co. KG
 Güldenwerther Bahnhofstraße 25–29,
 D-42857 Remscheid, Germany

* Valid from 1 September 2024 until 28 February 2025. Errors excepted. We accept no liability for printing errors! All rights reserved regarding technical modifications and errors. Images may not always correspond to originals and are thus non-binding! © 2024